



Equations and FORTRAN Program for the Canadian Forest Fire Weather Index System



**THE CANADIAN FORESTRY SERVICE
GOVERNMENT OF CANADA**

The Canadian Forestry Service is the principal source of federal expertise in forestry and has been designated as the government's lead agency for forestry matters. Its general objective is to promote the wise management and use of Canada's forest resources for the economic, social and environmental benefit of Canadians.

The following are the main functions of the CFS:

1. Coordination of federal policies for the promotion of better resource management and forest industry development.
2. Provision of scientific and technological leadership in forestry through research and development.
3. Provision and analysis of national and international statistics and information as a basis for policy formulation.
4. Development and certification of codes and standards for wood product performance.
5. Protection of Canada's forests from foreign pests.
6. Fostering the potential use of the forest resource for energy.
7. Contributing to the environmental objectives of the Government of Canada.

Canadian Forestry Service programs are coordinated with those of other forestry agencies through a variety of mechanisms, including the Canadian Council of Forestry Ministers, the Forest Sector Strategy Committee, management committees for Federal-Provincial Forestry Development programs, national and regional Research Advisory Committees, and various technical committees for specific program areas.

The Canadian Forestry Service is comprised of a headquarters unit, six forestry centres, and two national institutes. The forestry centres are responsive to regional priorities and maintain close liaison with the respective provincial government forestry departments and other clients. They also participate in, and frequently lead, national programs. The national institutes provide the focus for programs of national scope.

**SERVICE CANADIEN DES FORÊTS
GOUVERNEMENT DU CANADA**

Le Service canadien des forêts (SCF) réunit la majorité des spécialistes fédéraux en foresterie; il a été désigné comme l'organisme officiel du gouvernement responsable du secteur forestier. Son objectif général est de promouvoir l'aménagement et l'utilisation judicieuse des ressources forestières du Canada pour le plus grand bien économique, social et environnemental des Canadiens.

Voici les principales fonctions du SCF:

1. Coordonner les politiques fédérales afin de favoriser l'amélioration de la gestion des ressources et l'expansion de l'industrie forestière.
2. Fournir une orientation scientifique et technologique dans le domaine de la foresterie, par la recherche et le développement.
3. Fournir et analyser les statistiques et l'information nationales et internationales qui serviront à établir les politiques.
4. Mettre au point et homologuer des codes et des normes en matière de rendement des produits du bois.
5. Protéger les forêts canadiennes en luttant contre les ravageurs étrangers.
6. Parrainer l'utilisation éventuelle des ressources forestières pour la production d'énergie.
7. Adhérer aux objectifs environnementaux du gouvernement fédéral.

Les programmes du SCF sont menés de concert avec ceux d'autres organismes forestiers par l'entremise de divers mécanismes dont le Conseil canadien des ministres des Forêts, le Comité de la stratégie forestière, les comités de gestion des programmes fédéraux-provinciaux de développement forestier, les comités nationaux et régionaux consultatifs sur la recherche, de même que divers comités techniques axés sur des domaines de programmes spécifiques.

Le SCF comprend une administration centrale, six centres de foresterie et deux instituts nationaux. Les centres de foresterie doivent répondre aux impératifs régionaux et entretenir une liaison étroite avec les ministères provinciaux des Forêts. Ils participent également à des programmes nationaux dont ils assument fréquemment la direction. Les instituts nationaux sont les foyers des programmes d'envergure nationale.

Equations and FORTRAN Program for the Canadian Forest Fire Weather Index System

C.E. Van Wagner and T.L. Pickett
Petawawa National Forestry Institute

Canadian Forestry Service
Government of Canada
Forestry Technical Report 33
Ottawa 1985

©Minister of Supply and Services Canada 1985

ISBN 0-662-13906-2
Cat. No. Fo64-33/1985E

Additional copies of this publication are
available at no charge from:

Canadian Forestry Service
Place Vincent Massey, 3rd Floor
Ottawa, Ontario
K1A 1G5

A microfiche edition of this publication
may be purchased from:

Micromedia Ltd.
158 Pearl Street
Toronto, Ontario
M5H 1L3

Cette publication est aussi disponible en français sous
le titre *Équations et programme FORTRAN de l'Indice
Forêt-Météo de la méthode canadienne.*

First printing 1985
Second printing 1987

CONTENTS

	Page
Abstract	IV
Resumé . . .	IV
Introduction.	
Symbols in the Equations	3
Equations and Procedures.	5
Description of Program.	9
Symbols in the Program	11
Program F-32 .	12
Sample of Input . .	16
Sample of Output	17
References	. 18

ABSTRACT

Improved official equations are presented for the 1984 version of the Canadian Forest Fire Weather Index System. The most recent mathematical refinements serve to further rationalize the Fine Fuel Moisture Code and render it more compatible with other developments in the Canadian Forest Fire Danger Rating System. The effect of these changes is so slight that no problems are anticipated in converting from the previous version to this new one. Also given is a FORTRAN program intended as a standard for processing the equations in their most accurate mathematical form.

RÉSUMÉ

Ce rapport présente, en complément au système de l'Indice canadien forêt-météo, des équations connues qu'on a retouchées. Ces précisions mathématiques veulent rendre l'indice du combustible léger plus rationnel et davantage compatible avec les nouveaux développements que connaît la Méthode canadienne d'évaluation des dangers d'incendie de forêt. Il s'agit de changements mineurs qui ne devraient pas faire problème advenant qu'une équation de la version antérieure soit à convertir. Le programme FORTRAN se veut une base pour traiter des équations dans le plus pur langage mathématique.

INTRODUCTION

The present report is a companion to the fourth edition of the Tables for the Canadian Forest Fire Weather Index System (Canadian Forestry Service 1987). The equations on which this new edition is based are presented here. Also included is a computer program incorporating the mathematical routines leading to the Fire Weather Index (FWI). It is written in FORTRAN 77 to run on a DEC PDP-11/44. With proper modification it could be handled by many smaller computers.

The report is a replacement of Information Report PS-X-58 (Van Wagner and Pickett 1975¹), which listed equations for the 1976 version of the Fire Weather Index (FWI) System. The development and structure of the FWI System were described originally by Van Wagner (1974) in Canadian Forestry Service Publication 1333, but the mathematics in that paper are partly obsolete. Publication 1333 has now been replaced by Forestry Technical Report 35 (Van Wagner 1987).

The 1976 version of the FWI System listed the following mathematical changes from the original 1970 version:

1. Change in equation giving the equilibrium moisture content (EMC) during a wetting cycle in the Fine Fuel Moisture Code (FFMC), to eliminate an anomaly at very high relative humidity (RH);
2. Replacement of the original temperature correction in the FFMC with separate temperature effects on EMC and drying rate;
3. Increase in the amount of rain discarded in the Drought Code (DC) from 1.524 mm to 2.8 mm;
4. Change in the buildup function, $f(D)$, at Buildup Index (BUI) values over 80, in order to cause the FWI to level off in extreme drought.

Note: Further acronyms and symbols are defined in accompanying lists.

The additional mathematical changes in the present version further rationalize the structure of the FFMC. This code has worked adequately, but new developments in the Canadian Forest Fire Danger Rating System (CFFDRS), of which the FWI System is a part, create a need for a) realistic conversions from code value to actual fuel moisture, b) a common basis for the standard daily FFMC and its round-the-clock hourly version (Van Wagner 1977) and, c) ready modification for special purposes. Accordingly, the new FFMC incorporates the following alterations:

1. A new moisture scale, the FF-scale, with a higher maximum possible moisture content (250% instead of 101%);
2. A new rain-effect equation that operates on moisture content rather than on code value;
3. An adjusted drying rate that operates on the moisture content as expressed by the new moisture scale, but results in the same rate of change in code value as before;
4. A variable wetting rate when the EMC is higher than the initial moisture content, in place of the fixed rate used previously, and;
5. An adjustment of the fine fuel moisture function, $f(F)$, in the Initial Spread Index (ISI), to fit the new higher moisture conversion scale.

¹C.E. Van Wagner is a research scientist, and T.L. Pickett is a computer programmer at the Petawawa National Forestry Institute, Chalk River, Ontario K0J 1J0.

These changes have been accomplished with very little difference in the output of the system of equations. That is, the resulting codes and indexes will be sufficiently similar for daily use of the system to continue uninterrupted and for the statistical continuity of annual records to be preserved.

As before, the computer program is set up for the calculation at one time of an entire season's output for one station only. Its primary purpose is to illustrate the programming of the equations in order to give the purest possible mathematical output, with no artificial constraints or limits other than those required by the nature of the equations. It is intended to serve as a standard of comparison by which the output of any other program may be tested.

This 1984 version (as well as the previous version) includes the computation of the Daily Severity Rating (DSR), as described by Van Wagner (1970). The DSR is a function of the FWI specifically designed for averaging, either for any desired period of time at a single location, or as an area average of any number of locations. The FWI itself, on the other hand, is not considered suitable for averaging, and should be used as its single daily value only. The DSR averaged over a whole season, for example, would be called the Seasonal Severity Rating (SSR) and could be used for comparing fire weather from year to year, or fire climate from place to place.

SYMBOLS IN THE EQUATIONS

All quantities used in the numbered equations are represented in the following list by single letters, sometimes with subscripts. The symbols are arranged in groups according to their place in the whole. All moisture contents are percentages based on dry weight. Noon refers to standard time.

WEATHER

- noon temperature, °C
 - noon relative humidity, %
 - noon wind speed, km/h
 - r_o - rainfall in open, measured once daily at noon, mm
 - effective rainfall, FFMC
 - effective rainfall, DMC
 - effective rainfall, DC
-

FINE FUEL MOISTURE CODE (FFMC)

- m_o - fine fuel moisture content from previous day
 - fine fuel moisture content after rain
 - fine fuel moisture content after drying
 - fine fuel EMC for drying
 - fine fuel EMC for wetting
 - intermediate step in calculation of k_d
 - log drying rate, FFMC, $\log_{10}m/\text{day}$
 - intermediate step in calculation of k_w
 - log wetting rate, $\log_{10}m/\text{day}$
 - previous day's FFMC
 - FFMC
-

DUFF MOISTURE CODE (DMC)

- M_o - duff moisture content from previous day
 - duff moisture content after rain
 - duff moisture content after drying
 - log drying rate in DMC, $\log_{10}M/\text{day}$
 - effective day length in DMC, hours
 - slope variable in DMC rain effect
 - previous day's DMC
 - DMC after rain
 - DMC
-

DROUGHT CODE (DC)

Q – moisture equivalent of DC, units of 0.254 mm

Q_o – moisture equivalent of previous day's DC

Q_r – moisture equivalent after rain

– potential evapotranspiration, units of 0.254 mm water/day

– day-length adjustment in DC

D_o – previous day's DC

– DC after rain

– DC

FIRE BEHAVIOR INDEXES (ISI, BUI, FWI)

$f(W)$ – wind function

$f(F)$ – fine fuel moisture function

$f(D)$ – duff moisture function

R – Initial Spread Index (ISI)

U – Buildup Index (BUI)

B – FWI (intermediate form)

– FWI (final form)

SEVERITY RATING

DSR – Daily Severity Rating

EQUATIONS AND PROCEDURES

FINE FUEL MOISTURE CODE (FFMC)

$m_o = 147.2 (101 - F_o) / (59.5 + F_o)$	(1)
$r_f = r_o - 0.5,$	$r_o > 0.5$ (2)
$m_r = m_o + 42.5 r_f (e^{-100/(251 - m_o)})(1 - e^{-6.93/r_f}),$	$m_o \leq 150$ (3a)
$m_r = m_o + 42.5 r_f (e^{-100/(251 - m_o)})(1 - e^{-6.93/r_f}) + 0.0015 (m_o - 150)^2 r_f^{0.5},$	$m_o > 150$ (3b)
$E_d = 0.942 H^{0.679} + 11e^{(H-100)/10} + 0.18 (21.1 - T)(1 - e^{-0.115H})$	(4)
$E_w = 0.618 H^{0.753} + 10e^{(H-100)/10} + 0.18 (21.1 - T)(1 - e^{-0.115H})$	(5)
$k_o = 0.424 [1 - (H/100)^{1.7}] + 0.0694 W^{0.5} [1 - (H/100)^8]$	(6a)
$k_d = k_o \times 0.581 e^{0.0365T}$	(6b)
$k_1 = 0.424 [1 - (\frac{100-H}{100})^{1.7}] + 0.0694 W^{0.5} [1 - (\frac{100-H}{100})^8]$	(7a)
$k_w = k_1 \times 0.581 e^{0.0365T}$	(7b)
$m = E_d + (m_o - E_d) \times 10^{-k_d}$	(8)
$m = E_w - (E_w - m_o) \times 10^{-k_w}$	(9)
$F = 59.5 (250 - m) / (147.2 + m)$	(10)

The FFMC is calculated as follows:

1. Previous day's F becomes F_o .
2. Calculate m_o from F_o by Equation 1.
- 3a. If $r_o > 0.5$, calculate r_f by Equation 2.
- b. Calculate m_r from r_f and m_o by Equation 3a or 3b.
 - (i) If $m_o \leq 150$, use Equation 3a.
 - (ii) If $m_o > 150$, use Equation 3b.
- c. Then, m_r becomes the new m_o .
4. Calculate E_d by Equation 4.
- 5a. If $m_o > E_d$, calculate k_d by Equations 6a and 6b.
- b. Calculate m by Equation 8.
6. If $m_o < E_d$, calculate E_w by Equation 5.
- 7a. If $m_o < E_w$, calculate k_w by Equations 7a and 7b.
- b. Calculate m by Equation 9.
8. If $E_d \geq m_o \geq E_w$, let $m = m_o$.
9. Calculate F from m by Equation 10. This is today's FFMC.

There are two restrictions in the use of these equations: 1) Equation 3 (a or b) must not be used when $r_o \leq 0.5$ mm; that is, in dry weather the rainfall routine must be omitted. 2) m has an upper limit of 250; that is, when Equation 3 (a or b) yields $m_r > 250$, let $m_r = 250$.

DUFF MOISTURE CODE (DMC)

$r_e = 0.92r_o - 1.27,$	$r_o > 1.5$	(11)
$M_o = 20 + e^{(5.6348 - P_o/43.43)}$		(12)
$b = 100/(0.5 + 0.3 P_o),$	$P_o \leq 33$	(13a)
$b = 14 - 1.3 \ln P_o,$	$33 < P_o \leq 65$	(13b)
$b = 6.2 \ln P_o - 17.2,$	$P_o > 65$	(13c)
$M_r = M_o + 1000r_e/(48.77 + br_e)$		(14)
$P_r = 244.72 - 43.43 \ln (M_r - 20)$		(15)
$K = 1.894 (T + 1.1) (100 - H) L_e \times 10^{-6}$		(16)
$P = P_o \text{ (or } P_r) + 100K$		(17)

The DMC is calculated as follows

- 1 Previous day's P becomes P_o .
- 2a. If $r_o > 1.5$, calculate r_e by Equation 11.
 - b. Calculate M_o from P_o by Equation 12.
 - c. Calculate b by the appropriate one of Equations 13a, 13b, or 13c.
 - d. Calculate M_r by Equation 14.
 - e. Convert M_r to P_r by Equation 15. P_r becomes new P_o .
3. Take L_e from Table 1 below.
4. Calculate K by Equation 16.
5. Calculate P from P_o (or P_r) by Equation 17. This is today's DMC.

There are three restrictions on the use of the DMC equations: 1) Equations 11 to 15 are not used unless $r_o > 1.5$; that is, the rainfall routine must be omitted in dry weather. 2) P_r cannot theoretically be less than zero. Negative values resulting from Step 2e above must be raised to zero. 3) Values of T less than -1.1 must not be used in Equation 16. If $T < -1.1$, let $T = -1.1$.

Table 1
Effective day-lengths (L_e) for DMC

Month:	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec
L_e												

DROUGHT CODE (DC)

$r_d = 0.83r_o - 1.27,$	$r > 2.8$	(18)
$Q_o = 800e^{-D_o/400}$		(19)
$Q_r = Q_o + 3.937r_d$		(20)
$D_r = 400 \ln(800/Q_r)$		(21)
$V = 0.36 (T + 2.8) + L_f$		(22)
$D = D_o \text{ (or } D_r) + 0.5V$		(23)

The DC is calculated as follows:

1. Previous day's D becomes D_o .
- 2a. If $r_o > 2.8$, calculate r_d by Equation 18.
 - b. Calculate Q_o from D_o by Equation 19.
 - c. Calculate Q_r by Equation 20.
 - d. Convert Q_r to D_r by Equation 21. D_r becomes new D_o .
3. Take L_r from Table 2 below.
4. Calculate V by Equation 22.
5. Calculate D from D_o (or D_r) by Equation 23. This is today's DC.

There are four restrictions on the use of the DC equations: 1) Equations 18 to 21 are not used unless $r_o > 2.8$; that is, in dry weather the rainfall routine must be omitted. 2) D, cannot theoretically be less than zero. Negative values resulting from Step 2d above must be raised to zero. 3) Values of T less than -2.8 must not be used in Equation 22. If $T < -2.8$, let $T = -2.8$. 4) V cannot be negative. If Equation 22 produces a negative result, let $V = 0$.

Table 2
Day-length factors (L_r) for DC

Month:	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec
	-1.6	-1.6	-1.6									

INITIAL SPREAD INDEX (ISI)

$$f(W) = e^{0.05039W} \quad (24)$$

$$f(F) = 91.9e^{-0.1386m} [1 + m^{5.31}/(4.93 \times 10^7)] \quad (25)$$

$$R = 0.208 f(W) f(F) \quad (26)$$

BUILDUP INDEX (BUI)

$$U = 0.8 PD/(P + 0.4D), \quad P \leq 0.4D \quad (27a)$$

$$U = P - [1 - 0.8D/(P + 0.4D)][0.92 + (0.0114P)^{1.7}], \quad P > 0.4D \quad (27b)$$

FIRE WEATHER INDEX (FWI)

$$f(D) = 0.626U^{0.809} + 2, \quad U \leq 80 \quad (28a)$$

$$f(D) = 1000/(25 + 108.64 e^{-0.023U}), \quad U > 80 \quad (28b)$$

$$B = 0.1 R f(D) \quad (29)$$

$$\ln S = 2.72 (0.434 \ln B)^{0.647}, \quad B > 1 \quad (30a)$$

$$S = B, \quad B \leq 1 \quad (30b)$$

The ISI, BUI, and FWI are calculated as follows:

1. Calculate $f(W)$ and $f(F)$ by Equations 24 and 25.
2. Calculate R by Equation 26. This is today's ISI.
3. Calculate U by Equation 27a if $P \leq 0.4D$, or by Equation 27b if $P > 0.4D$. This is today's BUI.
4. Calculate $f(D)$ by Equation 28a for values of U up to 80. If $U > 80$, use Equation 28b.
5. Calculate B by Equation 29.
6. If $B > 1$, calculate S from its logarithm, given by Equation 30a. If $B \leq 1$, let $S = B$ according to Equation 30b. S is today's FWI.

DAILY SEVERITY RATING (DSR)

$$DSR = 0.0272 (FWI)^{1.77} \quad (31)$$

DESCRIPTION OF PROGRAM

The computer program presented here descends from one written by Simard (1970) at the former Forest Fire Research Institute. That program was designed to process weather data from many stations for a whole season. There was provision for missing data and for limits to guard against abnormal weather data. It was a complex program requiring, at the time, considerable computer capacity.

Simard's program was simplified by Engisch and Walker (1971) to handle one season's verified weather data for one station only, eliminating all unnecessary limits. Kean (1975) subsequently revised this program, incorporating several newly developed mathematical changes. However, the decision to convert to metric weather measurements rendered his version obsolete. Information Report PS-X-58 (Van Wagner and Pickett 1975) included the metric successor to Kean's program. The program listed in this report incorporates the mathematical changes described earlier, but is similar in usage to the one in PS-X-58.

To operate this program, enter first the starting month and the number of days of data in that month. For example, if the starting month is April and the first day is April 13, there will be data for 18 days in month 4, and the entry will be 418. Then enter the daily weather observations in order: temperature (°C), relative humidity (%), wind (km/h), and rain (mm). Temperature and rain are entered to the first decimal place; relative humidity and wind are entered in whole numbers. The option of entering weather data in Imperial units is provided, but the output converts them to metric.

The standard starting values of the three fuel moisture codes, namely FFMC 85, DMC 6, and DC 15, are incorporated in the program. However, the option of entering any desired starting values is also provided.

The output is listed in twelve columns: date (month and day), the four kinds of weather data, the three fuel moisture codes (FFMC, DMC, DC), the three fire behavior indexes (ISI, BUI, FWI), and the Daily Severity Rating (DSR). The computer stops automatically after the last day's weather. The program includes no limits on the input data other than those needed to prevent mathematical anomalies. All moisture codes are carried from day to day in precise floating-point format, as are all intermediate quantities leading to the daily FWI. The output is thus in the purest possible mathematical form and constitutes a reference against which calculations from other computer programs or from the FWI System Tables (Canadian Forestry Service 1984) may be compared.

The main uses of this standard program¹ are for development work on the FWI System, and for reference purposes as described previously. Operational programs designed for processing daily weather observations from many stations throughout a fire season will naturally have different input and output arrangements.

Two points warrant comment. The first is the degree of precision necessary when printing out the daily codes and indexes. The standard program rounds all codes and indexes to the nearest tenth, and prints them out to one decimal place. However, whole-number (i.e., integer) output is, no doubt, adequate for most operational purposes. In certain cases, the first decimal may be desirable for the FFMC (especially above 90), and for the ISI (especially below 10). The DSR is given to two decimal places, and is best used in that form.

The second comment refers to the precision with which the three moisture codes (FFMC, DMC, and DC) are carried over from day to day. The standard program carries over each day's code values in full floating-point format, equivalent to about seven significant figures (four or five decimal places). However, if computer storage capacity is a limiting factor, something less than perfect accuracy in output may be acceptable in operational use. Trials were made at three reduced levels of the precision to which the three moisture codes are carried over from day to day: 1) two decimals, 2) one decimal, and 3) integers. The results of two seasons' tests, as percentage of error-days in the output of each code and index, are listed in Table 3.

¹Designated Program F-32 (January 28, 1986). Enquiries may be directed to the Petawawa National Forestry Institute, Canadian Forestry Service, Chalk River, Ontario K0J 1J0

Table 3
Percent of days in which whole-number output of the FWI System components is in error at three levels of precision in the carryover of moisture codes from day to day. Compared with standard floating-point precision.

Component	2-decimal carryover	1-decimal carryover	Integer carryover (no decimals)			
	% of days in error by 1	% of days in error by 1	% of days in error by			
			1	2	3	1 or more
FFMC	—	1.9	6.2	—	—	6.2
	0.5	4.3	41.8	4.9		
					1.6	
				8.2	1.4	

Conclusions to be drawn from Table 3 are:

1. Carrying over the moisture codes with two decimal places provides nearly perfect accuracy of output except for occasional one-integer errors in the DC, which are of little consequence.
2. Carrying over one decimal place may be precise enough for some operational use. For example, one-integer errors would occur in the DMC on about one day in 25, in the FFMC on about one day in 50, and in the FWI on about one day in 200.
3. Carrying over the moisture codes as integers produces a generally inaccurate output, and is not recommended.

Of all the six components, the DC is the only one to exhibit an anomalous pattern in Table 3. Because the DC has limited power of self-correction in the mathematical sense compared with the FFMC and DMC, it tends to slip out of tune by one digit and to remain so for days on end. Considerably more sampling would be needed to establish its average pattern.

The standard program for the FWI System is listed in the following pages, followed by samples of input and output.

SYMBOLS IN THE PROGRAM

WEATHER

- T – temperature, °C
 - relative humidity, %
 - wind, km/h
 - R,RA – rain, mm
-

FINE FUEL MOISTURE CODE (FFMC)

- FO – starting or yesterday's FFMC
 - starting moisture content
 - today's final moisture content
 - EMC for drying
 - EMC for wetting
 - intermediate value of X
 - log drying or wetting rate
 - FFM – today's FFMC
-

DUFF MOISTURE CODE (DMC)

- PO – starting or yesterday's DMC
 - RK – drying factor
 - EL(J) – effective day-length for month J
 - RW – effective rain
 - DMC after rain
 - WMI – initial moisture content
 - WMR – moisture content after rain
 - B – function in rain effect
-

DROUGHT CODE (DC)

- DOT – starting or yesterday's DC
 - drying factor
 - FL(J) – day-length factor for month J
 - RW – effective rain
 - SMI – moisture equivalent of DC
 - DC after rain
-

FIRE BEHAVIOR INDEXES (ISI, BUI, FWI)

- FM – today's fine fuel moisture content
 - fine fuel moisture function
 - ISI
 - ratio function to correct BUI when less than DMC
 - DMC function to correct BUI when less than DMC
 - intermediate form of FWI
 - SL – logarithm of final FWI
 - DSR – Daily Severity Rating
-

PROGRAM F-32

```
C   PROGRAM NO.: F-32
C
C   STANDARD 1984 VERSION OF CANADIAN FOREST FIRE WEATHER INDEX SYSTEM
C   AS OF 28-JANUARY-1986.
C
C   WRITTEN IN FORTRAN 77.
C
C   READS WEATHER DATA IN EITHER ENGLISH OR METRIC UNITS AND PRINTS
C   OUT IN METRIC ONLY.
C
C   CODES AND INDEXES OUTPUT ALL TO ONE DECIMAL PLACE.
C   DAILY SEVERITY RATING OUTPUT TO TWO DECIMAL PLACES.
C
C   LMON = LENGTH OF MONTHS
C   EL = DMC DAY-LENGTH FACTORS
C   FL = DC DAY-LENGTH FACTORS
C
C   DIMENSION LMON(12), EL(12), FL(12),AST(2),TITLE(20)
C   LOGICAL*1 DAT(9),YES,YES1,ANS,ANS1
C   LOGICAL *1 INFMT(40)
C   TYPE 5
5  FORMAT(' INPUT FILENAME: eg: SAMPLE.DAT ', $)
ACCEPT 10, INFMT
10  FORMAT(40A1)
INFMT(40)=0
OPEN(UNIT=1,NAME=INFMT,TYPE='OLD',READONLY)
OPEN(UNIT=2,STATUS='NEW',NAME='F32OUT.DAT')
DATA LMON /31,28,31,30,31,30,31,31,30,31,30,31/
DATA EL /6.5,7.5,9.0,12.8,13.9,13.9,12.4,10.9,9.4,8.0,7.0,
*6.0/
DATA FL /-1.6,-1.6,-1.6,.9,3.8,5.8,6.4,5.0,2.4,.4,-1.6,-1.6/
DATA AST /' ','*' /
DATA ANS /'Y' /
TYPE 15
15  FORMAT(/1X,'ENTER VIA KEYBOARD EITHER 0 OR 1 '/1X'.....0
* IF DATA IS IN METRIC UNITS'/1X' OR 1 IF DATA IS IN
* ENGLISH UNITS')
READ(5,*) IUNIT
C
C   20 - METRIC FORMAT, 25 - ENGLISH FORMAT
C
C   20  FORMAT(F4.1,2I4,F5.1)
C   25  FORMAT(F4.0,2I4,F5.2)
C
C   READS IN STATION & YEAR.
C
C   READ(1,30) TITLE
C   30  FORMAT(20A4)
C
C   THIS SECTION ALLOWS FOR INITIAL VALUES OF FFMC, DMC, DC TO BE OPTIONAL
C
C   FO=85.0
C   PO=6.0
C   DOT=15.0
C   TYPE 35
35  FORMAT(' FFMC=85.0, DMC=6.0, DC=15.0; DO YOU WISH TO USE THESE
* INITIAL STANDARD VALUES? [Y/N] '$)
ACCEPT 10,ANS1
IF(ANS1.EQ.ANS) GO TO 55
TYPE 40
```

```

40 FORMAT(' FFMC (F4.1): ', $)
   ACCEPT 20,FO
   TYPE 45
45 FORMAT(' DMC (F4.1): ', $)
   ACCEPT 20,PO
   TYPE 50
50 FORMAT(' DC (F4.1): ', $)
   ACCEPT 20,DOT
C
C   READS STARTING MONTH OF THE YEAR AND NUMBER OF DAYS IN STARTING
C   MONTH.
C
55 READ(1,60) M, NDAYS
60 FORMAT(I1,I2)
   WRITE(2,65)
65 FORMAT(1H1'PROGRAM NO.: F-32')
   CALL DATE(DAT)
   WRITE(2,70) DAT,TITLE
70 FORMAT(1X,9A1///1X,20A4//)
   WRITE(2,75) FO,PO,DOT
75 FORMAT(' INITIAL VALUES FOR FFMC:',F5.1,',', DMC:',F5.1,',', DC:',F5.1,
*//)
   DO 290 J=M,12
   NN=LMON(J)
   IF(J.EQ.M) GO TO 80
   IDAYS=1
   GO TO 85
80 IDAYS=LMON(J)-NDAYS+1
C
C   READS DAILY WEATHER DATA
C
85 IAST=1
   DO 290 I=IDAYS,NN
   IF(IUNIT.EQ.0) GO TO 90
   READ(1;25,END=295) T,IH,IW,R
   W=IW
   GO TO 95
90 READ(1,20,END=295) T,IH,IW,R
   W=IW
95 IF(IUNIT.EQ.0) GO TO 100
   T=(T-32.)*5./9.
   W=W*1.609
   R=R*25.4
100 TX=T
   H=IH
   RAIN=R
   IF(IAST.GT.1) GO TO 110
   WRITE(2,105)
105 FORMAT(///,1X,' DATE TEMP RH WIND RAIN
* FFMC DMC DC
* ISI BUI FWI DSR'/)

```

C
C
C

FINE FUEL MOISTURE CODE

```
110 WMO=(147.2*(101-FO))/(59.5+FO)
    IF(R.GT.0.5) GO TO 115
    GO TO 125
115 RA=R-.5
    IF(WMO.GT.150.) GO TO 120
    WMO=WMO+42.5*RA*EXP(-100./(251.-WMO))*(1.-EXP(-6.93/RA))
    GO TO 125
120 WMO=(WMO+42.5*RA*EXP(-100./(251.-WMO))*(1.-EXP(-6.93/RA)))+
    *(0.0015*(WMO-150.)**2)*RA**.5
125 IF(WMO.GT.250.) WMO=250.
    ED=0.942*(H**0.679)+(11.*EXP((H-100.)/10.))+0.18*(21.1-T)
    *(1.-1./EXP(0.115*H))
    IF(WMO-ED) 130,135,140
130 EW=.618*(H**.753)+(10.*EXP((H-100.)/10.))+.18*(21.1-T)
    *(1.-1./EXP(0.115*H))
    IF(WMO.LT.EW) GO TO 145
135 WM=WMO
    GO TO 150
140 Z=0.424*(1.-(H/100.)**1.7)+(0.0694*(W**0.5))*(1.-(H/100.)**8)
    X=Z*(0.581*(EXP(0.0365*T)))
    WM=ED+(WMO-ED)/10.**X
    GO TO 150
145 Z=.424*(1.-((100.-H)/100.)**1.7)+(.0694*(W**.5))*(1.-((100.-H)
    */100.)**8)
    X=Z*(.581*(EXP(.0365*T)))
    WM=EW-(EW-WMO)/10.**X
150 FFM=(59.5*(250.-WM))/(147.2+WM)
    IF(FFM.GT.101.) GO TO 155
    IF(FFM) 160,165,165
155 FFM=101.
    GO TO 165
160 FFM=0.0
```

C
C
C

DUFF MOISTURE CODE

```
165 IF(T+1.1.GE.0.) GO TO 170
    T=-1.1
170 RK=1.894*(T+1.1)*(100.-H)*(EL(J)*0.0001)
175 IF(R.GT.1.5) GO TO 180
    PR=PO
    GO TO 205
180 RA=R
    RW=0.92*RA-1.27
    WMI=20.0+280./EXP(0.023*PO)
    IF(PO.LE.33.) GO TO 185
    IF(PO-65.) 190,190,195
185 B=100./(0.5+0.3*PO)
    GO TO 200
190 B=14.-1.3*ALOG(PO)
    GO TO 200
195 B=6.2*ALOG(PO)-17.2
200 WMR=WMI+(1000.*RW)/(48.77+B*RW)
    PR=43.43*(5.6348-ALOG(WMR-20.))
205 IF(PR.GE.0.) GO TO 210
    PR=0.0
210 DMC=PR+RK
```

```

C
C   DROUGHT CODE
C
  IF(T+2.8.GE.0.) GO TO 215
    T=-2.8
215  PE=(.36*(T+2.8)+FL(J))/2.
    IF(R.LE.2.8) GO TO 225
    RA=R
    RW=0.83*RA-1.27
C   SMI=800.*EXP(-DOT/400.)
C   DR=DOT-400.*ALOG(1.+((3.937*RW)/SMI))
C   IF(DR.GT.0.) GO TO 220
C   DR=0.0
220  DC=DR+PE
    GO TO 230
225  DR=DOT
    GO TO 220
230  IF(DC.GE.0.) GO TO 235
    DC=0.0

C
C   INITIAL SPREAD INDEX, BUILDUP INDEX, FIRE WEATHER INDEX
C
235  FM=(147.2*(101.-FFM))/(59.5+FFM)
    SF=19.115*EXP(FM*(-.1386))*(1.+(FM**5.31)/4.93E07)
    SI=SF*EXP(0.05039*W)
240  IF(DMC.EQ.0.0.AND.DC.EQ.0.0) GO TO 245
    BUI=(0.8*DC*DMC)/(DMC+0.4*DC)
    GO TO 250
245  BUI=0.
250  IF(BUI.GE.DMC) GO TO 255
    P=(DMC-BUI)/DMC
    CC=0.92+(0.0114*DMC)**1.7
    BUI=DMC-(CC*P)
    IF(BUI.LT.0.) BUI=0.
255  IF(BUI.GT.80.) GO TO 260
    BB=0.1*SI*(0.626*BUI**0.809+2.)
    GO TO 265
260  BB=0.1*SI*(1000./(25.+108.64/EXP(0.023*BUI)))
265  IF(BB-1.0.LE.0.) GO TO 270
    SL=2.72*(0.434*ALOG(BB))**0.647
    FWI=EXP(SL)
    GO TO 275
270  FWI=BB
275  DSR = 0.0272*FWI**1.77
280  IW=W+0.5
    WRITE(2,285) J,I,IX,IH,IW,RAIN,FFM,DMC,DC,SI,BUI,FWI,DSR
285  FORMAT(1X,2I3,F6.1,I4,I6,F7.1,F7.1,F6.1,F7.1,3F6.1,F8.2)
    FO=FFM
    PO=DMC
    DOT=DC
    IAST=IAST+1
290  CONTINUE
295  TYPE 300
300  FORMAT(/1X'OUTPUT IN F32OUT.DAT AND MUST BE SPOOLED
    * TO THE LINE PRINTER.'//)
305  STOP
    END

```

```

C
C   DROUGHT CODE
C
  IF(T+2.8.GE.0.) GO TO 215
    T=-2.8
215  PE=(.36*(T+2.8)+FL(J))/2.
    IF(R.LE.2.8) GO TO 225
    RA=R
    RW=0.83*RA-1.27
C   SMI=800.*EXP(-DOT/400.)
C   DR=DOT-400.*ALOG(1.+((3.937*RW)/SMI))
C   IF(DR.GT.0.) GO TO 220
C   DR=0.0
220  DC=DR+PE
    GO TO 230
225  DR=DOT
    GO TO 220
230  IF(DC.GE.0.) GO TO 235
    DC=0.0

C
C   INITIAL SPREAD INDEX, BUILDUP INDEX, FIRE WEATHER INDEX
C
235  FM=(147.2*(101.-FFM))/(59.5+FFM)
    SF=19.115*EXP(FM*(-.1386))*(1.+(FM**5.31)/4.93E07)
    SI=SF*EXP(0.05039*W)
240  IF(DMC.EQ.0.0.AND.DC.EQ.0.0) GO TO 245
    BUI=(0.8*DC*DMC)/(DMC+0.4*DC)
    GO TO 250
245  BUI=0.
250  IF(BUI.GE.DMC) GO TO 255
    P=(DMC-BUI)/DMC
    CC=0.92+(0.0114*DMC)**1.7
    BUI=DMC-(CC*P)
    IF(BUI.LT.0.) BUI=0.
255  IF(BUI.GT.80.) GO TO 260
    BB=0.1*SI*(0.626*BUI**0.809+2.)
    GO TO 265
260  BB=0.1*SI*(1000./(25.+108.64/EXP(0.023*BUI)))
265  IF(BB-1.0.LE.0.) GO TO 270
    SL=2.72*(0.434*ALOG(BB))**0.647
    FWI=EXP(SL)
    GO TO 275
270  FWI=BB
275  DSR = 0.0272*FWI**1.77
280  IW=W+0.5
    WRITE(2,285) J,I,IX,IH,IW,RAIN,FFM,DMC,DC,SI,BUI,FWI,DSR
285  FORMAT(1X,2I3,F6.1,I4,I6,F7.1,F7.1,F6.1,F7.1,3F6.1,F8.2)
    FO=FFM
    PO=DMC
    DOT=DC
    IAST=IAST+1
290  CONTINUE
295  TYPE 300
300  FORMAT(/1X'OUTPUT IN F32OUT.DAT AND MUST BE SPOOLED
    * TO THE LINE PRINTER.'//)
305  STOP
    END

```

SAMPLE OF INPUT

FWI TEST DATA APRIL 13 TO MAY 31
418

4 indicates starting month, in this case April.
18 indicates no. of days in starting month.

17.	42	25		- April 13
20.	21	25	2.4	
8.5	40	17		
6.5	25	6		
13.	34	24		
6.	40	22	0.4	
5.5	52	6		
8.5	46	16		
9.5	54	20		
7.	93	14	9.0	
6.5	71	17	1.0	
6.	59	17		
13.	52	4		
15.5	40	11		
23.	25	9		
19.	46	16		- April 30
18.	41	20		- May 1
14.5	51	16		
14.5	69	11		
15.5	42	8		
21.	37	8		
23.	32	16		
23.	32	14		
27.	33	12		
28.	17	27		
23.5	54	20		
16.	50	22	12.2	
11.5	58	20		
16.	54	16		
21.5	37	9		
14.	61	22	0.2	
15.	30	27		
20.	23	11		
14.	95	3	16.4	
20.	53	4	2.8	
19.5	30	16		
25.5	51	20	6.0	
10.	38	24		
19.	27	16		
26.	46	11	4.2	
30.	38	22		
25.5	67	19	12.6	
12.	53	28	11.8	
21.	38	8		
13.	70	20	3.8	
9.	78	24	1.4	
11.	54	16		
15.5	39	9		
18.	36	5		- May 31

Temperature °C Relative Humidity % Wind km/h Rain mm

SAMPLE OF OUTPUT

PROGRAM NO.: F-32

FWI TEST DATA APRIL 13 TO MAY 31

INITIAL VALUES FOR FFMC: 85.0, DMC: 6.0, DC: 15.0

DATE	TEMP	RH	WIND	RAIN	FFMC	DMC	DC	ISI	BUI	FWI	DSR
4 13	17.0	42	25	0.0	87.7	8.5	19.0	10.9	8.5	10.1	1.63
4 14	20.0	21	25	2.4	86.2	10.4	23.6	8.8	10.4	9.3	1.40
4 15	8.5	40	17	0.0	87.0	11.8	26.1	6.5	11.7	7.6	0.98
4 16	6.5	25	6	0.0	88.8	13.2	28.2	4.9	13.1	6.2	0.68
4 17	13.0	34	24	0.0	89.1	15.4	31.5	12.6	15.3	14.8	3.22
4 18	6.0	40	22	0.4	88.7	16.5	33.5	10.7	16.4	13.5	2.71
4 19	5.5	52	6	0.0	87.4	17.2	35.4	4.0	17.1	5.9	0.62
4 20	8.5	46	16	0.0	87.4	18.5	37.9	6.6	18.4	9.7	1.50
4 21	9.5	54	20	0.0	86.8	19.7	40.6	7.4	19.6	11.0	1.89
4 22	7.0	93	14	9.0	29.9	10.1	29.5	0.0	10.9	0.0	0.00
4 23	6.5	71	17	1.0	49.4	10.7	31.6	0.4	11.6	0.2	0.00
4 24	6.0	59	17	0.0	67.3	11.4	33.7	1.3	12.3	0.9	0.02
4 25	13.0	52	4	0.0	77.8	13.0	37.0	1.1	13.9	0.8	0.02
4 26	15.5	40	11	0.0	85.5	15.4	40.7	3.9	15.9	5.5	0.56
4 27	23.0	25	9	0.0	91.5	19.8	45.8	8.4	19.8	12.2	2.27
4 28	19.0	46	16	0.0	89.9	22.5	50.2	9.5	22.4	14.3	3.02
4 29	18.0	41	20	0.0	90.0	25.2	54.4	11.7	25.1	17.7	4.40
4 30	14.5	51	16	0.0	88.4	27.0	57.9	7.7	27.0	13.3	2.65
5 1	14.5	69	11	0.0	85.7	28.3	63.0	4.0	28.2	8.0	1.08
5 2	15.5	42	8	0.0	87.4	30.8	68.2	4.4	30.8	9.1	1.35
5 3	21.0	37	8	0.0	89.4	34.5	74.3	5.9	34.4	12.3	2.30
5 4	23.0	32	16	0.0	91.0	38.8	80.9	11.1	38.7	21.0	5.96
5 5	23.0	32	14	0.0	91.2	43.1	87.4	10.3	43.0	21.1	5.99
5 6	27.0	33	12	0.0	91.7	48.1	94.7	9.9	47.9	21.7	6.30
5 7	28.0	17	27	0.0	95.2	54.5	102.1	34.5	54.3	52.6	30.20
5 8	23.5	54	20	0.0	89.7	57.4	108.8	11.3	57.2	25.9	8.61
5 9	16.0	50	22	12.2	62.2	29.9	91.8	1.4	33.0	3.0	0.19
5 10	11.5	58	20	0.0	76.7	31.3	96.3	2.3	34.5	5.4	0.55
5 11	16.0	54	16	0.0	83.5	33.4	101.6	3.8	36.7	8.9	1.31
5 12	21.5	37	9	0.0	88.7	37.1	107.8	5.6	39.9	12.8	2.46
5 13	14.0	61	22	0.2	86.7	38.7	112.8	8.1	41.6	17.3	4.24
5 14	15.0	30	27	0.0	89.6	41.7	117.9	15.9	44.2	28.8	10.44
5 15	20.0	23	11	0.0	92.1	45.9	123.9	10.1	47.7	21.9	6.40
5 16	14.0	95	3	16.4	21.3	20.1	97.0	0.0	26.5	0.0	0.00
5 17	20.0	53	4	2.8	51.0	18.3	103.0	0.2	25.3	0.2	0.00
5 18	19.5	30	16	0.0	82.3	22.1	108.9	3.3	29.3	6.8	0.81
5 19	25.5	51	20	6.0	75.4	16.4	106.4	2.1	23.7	3.8	0.29
5 20	10.0	38	24	0.0	84.3	18.2	110.6	6.4	25.8	11.3	1.99
5 21	19.0	27	16	0.0	90.3	22.1	116.4	10.0	29.9	17.2	4.19
5 22	26.0	46	11	4.2	77.6	18.7	117.7	1.6	26.8	2.9	0.18
5 23	30.0	38	22	0.0	90.2	23.8	125.5	13.4	32.3	22.0	6.49
5 24	25.5	67	19	12.6	65.3	13.1	108.5	1.4	20.2	1.9	0.08
5 25	12.0	53	28	11.8	55.4	7.7	91.6	1.2	12.8	0.8	0.02
5 26	21.0	38	8	0.0	80.8	11.3	97.8	1.9	17.6	2.6	0.14
5 27	13.0	70	20	3.8	61.7	8.4	97.9	1.2	13.8	0.9	0.02
5 28	9.0	78	24	1.4	64.5	9.0	101.9	1.7	14.7	2.0	0.09
5 29	11.0	54	16	0.0	77.6	10.5	106.3	2.0	16.8	2.8	0.17
5 30	15.5	39	9	0.0	85.4	13.1	111.5	3.5	20.3	5.8	0.61
5 31	18.0	36	5	0.0	88.5	16.3	117.1	4.4	24.2	7.9	1.06

REFERENCES

- Canadian Forestry Service. 1987. Tables for the Canadian Forest Fire Weather Index System. Environ. Can., Can. For. Serv., For. Tech. Rep. 25 (4th ed.). 48 p.
- Engisch, R.L.; Walker, J.D. 1971. PDP-8L version of Simard's Fire Weather Index Program. Environ. Can., Can. For. Serv., Petawawa Forest Exp. Sta., Intern. Rep. PS-23. 10 p.
- Kean, W.A. 1975. A PDP-8L program for calculating the Fire Weather Index. Environ. Can., Can. For. Serv., Petawawa Forest Exp. Sta., Inf. Rep. PS-X-57. 12 p.
- Simard, A.J. 1970. Computer program to calculate the Canadian Forest Fire Weather Index. Environ. Can., Can. For. Serv., Forest Fire Res. Inst., Intern. Rep. FF-12. 18 p.
- Van Wagner, C.E. 1970. Conversion of Williams' severity rating for use with the Fire Weather Index. Environ. Can., Can. For. Serv., Petawawa Forest Exp. Sta., Inf. Rep. PS-X-21. 5 p.
- Van Wagner, C.E. 1974. Structure of the Canadian Forest Fire Weather Index. Environ. Can., Can. For. Serv., Pub. No. 1333. 44 p.
- Van Wagner, C.E. 1977. A method of computing fine fuel moisture content throughout the diurnal cycle. Environ. Can., Can. For. Serv., Petawawa Forest Exp. Sta. Inf. Rep. PS-X-69. 15 p.
- Van Wagner, C.E. 1987. Development and structure of the Canadian Forest Fire Weather Index System. Can. For. Serv., For. Tech. Rep. 35. 37 p.
- Van Wagner, C.E.; Pickett, T.L. 1975. Equations and Fortran IV program for the 1976 metric version of the Forest Fire Weather Index. Can. For. Serv., Petawawa Forest Exp. Sta., Inf. Rep. PS-X-58. 20 p.